

Utilization of Plastic waste in Bitumen Mixes for Flexible Pavement

Aditya Lakhera
(Asth. Prof.) Department of Civil Engineering
Shri Krishna University, Chhatarpur (MP)

ABSTRACT

Plastic garbage and how it is disposed of pose a serious risk to the environment, contributing to pollution and global warming. Adding plastic debris to bituminous mixes improves both their strength and properties. It will also provide a solution for the disposal of plastic and other pavement flaws such as ruts, pot holes, and corrugation. Polyethylene, Polystyrene, and Polypropylene waste plastics are used. The left over plastic is shredded, covered in aggregate, combined with heated bitumen, and used to create a mixture for paving. In addition to strengthening the pavement, this will lengthen its life span. The smoke from the cars will be absorbed by the titanium dioxide, which is utilized as a smoke absorbent substance. The hot, humid weather in India will benefit greatly from this novel technique. It is affordable.

KEYWORDS

Pavement, Thermoplastics, Bitumen, Environment, Pollution

1.0 INTRODUCTION

The major threat to the environment is the disposal of waste plastic. In a highway, the potholes and corrugation is the major problem. Plastic pavement will be a better solution to the above stated problems. A material that contains one or more organic polymer of large molecular weight, solid in its finished state, can be shaped by its flow is called as "plastic". The durability of plastic is high and it degrades very slowly. And also plastic has high resistance to degradation. Plastic can be divided into two major categories- thermosets & thermoplastics. Thermosets have high durability and strength because they solidify irreversibly when heated, henceforth can be used primarily in construction application. Plastic is a non-degradable waste, causes greenhouse effect and global warming. The various experiments have been carried out whether the waste plastic can be reused productively. The various literature indicated that the waste plastic when added to hot aggregates will form a fine coat of plastic over the aggregate and such aggregates when mixed with binder is found to have higher strength, higher resistance and better performance over a period of time. Along with bitumen, use waste plastic increases its life and smoothness. It is economical and eco-friendly. Addition of plastic waste in construction of pavements reduces the plastic shrinkage and drying shrinkage. The use of waste plastic improves the abrasion & slip resistance of asphalt pavement. In India, because of hot and extremely humid climate, plastic pavements of greatest advantage. In order to absorb the smoke from the vehicles; titanium dioxide

can be used. It also enhances the mechanical properties of the plastic, resulting in higher strength and high resistance.

2.0 OBJECTIVE

The objectives of this project are:

- To carry out the soil test.
- To design the flexible pavement
- To design the asphalt pavement with aggregate- plastic- bitumen mix.
- To coat the aggregate with plastic and incorporate titanium di-oxide.
- To test the bitumen and the modified bitumen.

3.0 SCOPE OF THE PROJECT

- To eradicate potholes
- To minimize the global warming , greenhouse gases and pollution.
- The lifespan of the roads can be increased
- Eco-friendly in nature.

3.1 Plastics Roads - General Introduction Plastic use in road construction is not new. It is already in use as PVC or HDPE pipe mat crossings built by cabling together PVC (polyvinyl chloride) or HDPE (high-density poly-ethylene) pipes to form plastic mats. The plastic roads include transition mats to ease the passage of tyres up to and down from the crossing. Both options help protect wetland haul roads from rutting by distributing the load across the surface. But the use of plastic-waste has been a concern for scientists and engineers for a quite long time. Recent studies in this direction have shown some hope in terms of using plastic-waste in road construction i.e., Plastic roads. A Bangalore-based firm and a team of engineers from R. V. College of Engineering, Bangalore, have developed a way of using plastic waste for road construction. An initial study was conducted in 1997 by the team to test for strength and durability. Plastic roads mainly use plastic carry-bags, disposable cups and PET bottles that are collected from garbage dumps as an important ingredient of the construction material. When mixed with hot bitumen, plastics melt to form an oily coat over the aggregate and the mixture is laid on the road surface like a normal tar road.

3.1.1 Advantages

- Reduce the need of bitumen by around 10%.
- Develop a technology which is eco-friendly.
- Improvements in fatigue life of roads.
- Increase the strength and better performance of the road.
- Use higher percentage of plastic waste.
- The gases released during traffic conditions are absorbed by smoke absorbent.

3.1.2 Disadvantages

- Toxic present in the co-mingled plastic wastes would start leaching.
- But the presence of chlorine will definitely release HCL gas.

4.0 LITERATURE REVIEW

Dr. R. Vasudevan (2007) - stated that the polymer bitumen blend is a better binder compared to plain bitumen. Blend has increased softening point and decreased Penetration value with a suitable ductility.

Zahra Niloofar Kalantar (2012) - Many researches on PMA mixture have been conducted for the past two decades. Although addition of virgin polymers to asphalt for the purpose of enhancing the properties of asphalt over a wide temperature range in paving applications was contemplated quite some time ago, recycled polymer added to asphalt have also shown almost the same result in improving the road pavement performance as compared to virgin polymers. This paper is a review of the use of polymers in asphalt pavement. In this study, a critical review on the history and benefits of using waste and virgin polymer in asphalt is presented followed by a review of general studies on using polymers in asphalt in order to improve the properties of pavement.

Amit Gawande (2012) - The quantum of plastic waste in municipal solid waste (MSW) is increasing due to increase in population, urbanization, development activities and changes in life style which leading widespread littering on the landscape. Thus disposal of waste plastic is a menace and become a serious problem globally due to their non-biodegradability and un aesthetic view. Since these are not disposed scientifically & possibility to create ground and water pollution. This waste plastic partially replaced the conventional material to improve desired mechanical characteristics for particular road mix. In conventional road making process bitumen is used as binder. Such bitumen can be modified with waste plastic pieces and bitumen mix is made which can be used as a top layer coat of flexible pavement. This waste plastic modified bitumen mix show better binding property, stability, density and more resistant to water.

Sunil J. Kulkarni (2015) - Minimization of waste material is important aspect of the modern growth and development initiatives⁴ . Plastic is used in various domestic and industrial applications. Use of plastic bags and bottles is very common. The disposal of plastic waste is major problem due to non-biodegradable nature of plastic. The plastic can be used as feedstock for ethanol like products. It can be used for road construction and other construction related activities. The current review summarizes the research on use of waste plastic.

Rishi Singh Chhabra (2021) - In the highway infrastructure, a large number of originates materials and technologies have been invented to determine their suitability for the design, construction and maintenance of these pavements. Plastics and rubbers are one of them. Also considering the environmental approach, due to excessive use of polythene in day to day business, the pollution to the environment is enormous. The use of plastic materials such as carry bags, cups, etc. is constantly increasing day by day¹⁰. Since the polythene are not biodegradable, the need of the current hour is to use the waste polythene in some beneficial purposes. The use of these materials as a road construction proves eco-friendly, economical and use of plastic gives strength in the sub-base course of the pavement.

5.0 COMPARATIVE STUDY

5.1 Central Mixing Plant (CMP) - The dry process can also be carried out using central mixing plant. The shredded plastic is added along with the aggregate in the conveyor belt. This is transferred into the hot cylinder. There aggregate is coated with plastic first and then with the bitumen. The mixer so prepared is then loaded in the dipper lorry and transported for road laying. CMP helps to have better control of temperature and better mixing of this material thus helping to have a uniform coating. This is adopted in our project. The comparative study is done by testing the normal aggregates & plastic coated aggregates, and the bitumen and modified bitumen (10% of bitumen replaced by plastic). The various tests that are carried out for the comparative study are

- Test on aggregates
 - i. Aggregate crushing test
 - ii. Los Angeles abrasion test
 - iii. Impact test

- Test on bitumen
 - i. Penetration test
 - ii. Softening point test
 - iii. Viscosity test
 - iv. Marshall Stability test.

6.0 TESTS ON AGGREGATES

6.1 Aggregate Crushing Test - The strength of the coarse aggregate may be assessed by aggregate crushing test. The aggregate crushing value provides a relative measure of resistance to crushing under gradually applied compressive load. To achieve a high quality of pavement, aggregates possessing high resistance to crushing or low aggregate crushing value re preferred.

6.2 Abrasion Tests - Due to the movements of traffic, the road stones used in the surface course are subjected to wearing action at the top. Hence road stones should be hard enough to resist the abrasion due to traffic. Abrasion tests are carried out to test the hardness property of stones and to decide whether they are suitable for the different road construction works. The abrasion test on aggregate may be carried out using any one of the following three tests –

- Los Angeles abrasion test
- Deval abrasion test
- Dory abrasion test

6.3 Los Angeles Abrasion Test - The principle of Los Angeles abrasion test is to find the percentage wear due to the relative rubbing action between the aggregate and steel balls used as abrasive charge. Pounding action of these balls also exists during the test and hence the resistance to wear and impact is evaluated by this test.

6.4 Tests on Bitumen penetration Test - Penetration test is to determine the hardness of the bitumen. The penetration of a bitumen is the distance in tenths of millimeter that a standard needle will penetrate into the bitumen under a load of 100gm applied for 4 seconds at 25⁰ c. penetration value indicates the softness of bitumen higher the penetration softer is the bitumen).

6.5 Softening Point Test - The principle behind this test is that softening point is the temperature at which the substance attains a particular degree of softening under specified condition of the test. Softening point denotes the temperature at which the bitumen attains a particular degree of softening under the specifications of this test. The test is conducted by ring and ball apparatus. A brass ring containing test sample of bitumen is suspended in liquid like water or glycerine at a given temperature. A steel ball is placed upon the bitumen sample and the liquid medium is heated at a rate of C minute. Temperature is noted when the softened bitumen touches the metal plate which is at a specified distance below. Generally, higher softening point indicates lower temperature susceptibility and is preferred in hot climates.

6.6 Viscosity Test - Viscosity is defined as the inverse of fluidity. Viscosity thus defines the fluid property of bituminous material. Viscosity is the general term for consistency and is the measure of resistance to flow. Many researchers believe that grading of bitumen should be by absolute viscosity units instead of the conventional penetration units.

7.0 RESULT AND DISUSSION

The crushing value reduces from 23.32 to 14.22 for normal and plastic coated aggregate. The value was reduced by 40%. Lower the aggregate crushing value higher is the strength. The aggregate impact value of plastic coated aggregate was reduced by 9% than the normal aggregate. It's the higher toughness of plastic coated aggregates. Los Angeles abrasion value

indicates the hardness of the aggregates. The abrasion value plastic coated aggregates were 21% less than the normal aggregates. The penetration value of bitumen is higher than the bitumen mixed with the plastic. The bitumen softens 10oC less than the bitumen replaced with plastic. The stability of modified bitumen (10% bitumen replaced by plastic) is higher than the normal bitumen.

8.0 CONCLUSION

For the roads to function better, plastic is combined with bitumen and aggregates. The aggregates' polymer coating lessens the voids and moisture absorption. As a consequence, there are few ruts and no potholes emerge. Compared to flexible pavement, plastic pavement is more durable and can handle heavy traffic. By using plastic mix, bitumen content can be decreased by 10% while road performance and strength are improved. Eco-friendly is this innovative technology. Vehicle pollution can be decreased by using combustion absorbent material (titanium dioxide) at a 10% polymer concentration.

9.0 REFERENCES

1. Indian Roads Congress IRC: 37-2012 - Guidelines for the design of flexible pavements- August 2012
2. R. Vasudevan "A technique to dispose waste plastics in an ecofriendly way – Application in construction of flexible pavements" Construction and Building Materials Vol. 8 Department of Chemistry, Thiagarajar College of Engineering, Madurai, Tamil Nadu, India, pp 311–320.
3. Miss Apurva J Chavan - Use of plastic waste in flexible Pavements -ISSN 2319 – 4847, Volume 2, Issue 4, April 2013
4. S.S.Verma - Roads from plastic waste - The Indian Concrete Journal - November 2008
5. Vinoth.N - Use of plastic wastes in road construction – Central Institutes of Plastic Engineering and technology
6. "Pavement design with central plant hot-mix recycled asphalt mixes", Construction and Building Materials, Vol. 21, Dept. of Civil Engg., Indian Institute of Technology, Kanpur, India, pp 928–936